

ETP406-PU Flexible ducts with polyurethane sheet



Description :

Flexible duct made of polyurethane sheet (PU) and galvanized steel (LZ) or copper plated (LR) wire helix (0.40mm thickness)

Characteristics :

Colour : transparent
 Temperature range: from -40°C to +90°C (+125°C peaks)
 Axial compressibility : 8:1

Size:

Standard 10 meters (20 meters roll up to Ø200 on request).

Use :

Suction and delivery of air, fumes, dust, textile fibres, sawdust and light chips.

Feature of this tube is the great flexibility and compressibility. Corrugated inner surface, high resistance to abrasion and tear.

Versions :

ETP406-PU-LZ : with galvanized steel wire helix
 ETP406-PU-LR : with copper plated steel wire helix

Price list

a.r. : price on request

internal ø	ETP406-PU-LZ	internal ø	ETP406-PU-LZ	internal ø	ETP406-PU-LR	internal ø	ETP406-PU-LR
	euro		euro		euro		euro
60	∨	140	∨	60	∨	140	∨
63	∨	150	∨	63	∨	150	∨
70	∨	152	∨	70	∨	152	∨
76	∨	160	∨	76	∨	160	∨
80	∨	170	∨	80	∨	170	∨
82	∨	180	∨	82	∨	180	∨
90	∨	200	∨	90	∨	200	∨
100	∨	203	∨	100	∨	203	∨
102	∨	225	∨	102	∨	225	∨
110	∨	250	∨	110	∨	250	∨
120	∨	275	∨	120	∨	275	∨
127	∨	300	∨	127	∨	300	∨
130	∨	305	∨	130	∨	305	∨