

# ETP407-PU Flexible ducts with polyurethane sheet



## Description :

Flexible duct made of 0.40mm thick polyurethane sheet (PU) and galvanized steel (LZ) or copper plated (LR) wire helix.

## Characteristics :

Colour: transparent  
 Temperature range: from -40°C to +90°C (+125°C peaks)  
 Axial compressibility : 8:1

## Size:

Standard 10 meters (20 meters roll up to Ø200 on request).

## Use :

- Suction of chips, wood and other material dust, pneumatic conveyance of textile fibres, paper, etc.
- Suction of pharmaceutical ingredients, foodstuff and powder food components.
- Installation in organic/chemical systems.

Peculiar characteristic of this tube is the great resistance to abrasion and cutting (5/6 times greater than rubber and 7 times more than PVC).

## Versions :

ETP407-PU-LZ : with galvanized steel wire helix  
 ETP407-PU-LR : with copper plated steel wire helix

## Price list

internal ø	ETP407-PU-LZ	internal ø	ETP407-PU-LZ	internal ø	ETP407-PU-LR	internal ø	ETP407-PU-LR
	euro		euro		euro		euro
40	∨	150	∨	40	∨	150	∨
50	∨	160	∨	50	∨	160	∨
60	∨	170	∨	60	∨	170	∨
63	∨	180	∨	63	∨	180	∨
70	∨	200	∨	70	∨	200	∨
76	∨	225	∨	76	∨	225	∨
80	∨	250	∨	80	∨	250	∨
90	∨	275	∨	90	∨	275	∨
100	∨	300	∨	100	∨	300	∨
110	∨	315	∨	110	∨	315	∨
120	∨	350	∨	120	∨	350	∨
125	∨	400	∨	125	∨	400	∨
130	∨	450	∨	130	∨	450	∨
140	∨	500	∨	140	∨	500	∨