

# ETP80-PU Flexible ducts with polyurethane sheet



## Description :

Flexible duct made of polyurethane (PU) sheet and copper plated steel wire helix (0,60 mm thickness).

## Characteristics :

Colour : transparent (blue or black on request)  
 Temperature range: from -40°C to +90°C (+125°C peaks)  
 Axial compressibility : 3:1

## Size:

Standard 20 meters. From the diameter 250mm 10 meters.

## Use :

- aspiration of chippings, wood and other material dust
- pneumatic transport of textile fibres and paper
- aspiration of pharmaceutical ingredients, foodstuff and powder food components.
- Installation in organic/chemical systems.

Peculiar characteristic of this tube is the great resistance to abrasion and cutting (5/6 times greater than rubber and 7 times more than PVC).

## Price list

The length of the hose should be considered in a extended position and at environment temperature (16/18°C - tolerance ±2%)

Item normally available from stock

internal ø	ETP80-PU	internal ø	ETP80-PU	internal ø	ETP80-PU	internal ø	ETP80-PU	internal ø	ETP80-PU
	euro		euro		euro		euro		euro
40	✓	90	✓	140	✓	225	✓	450	✓
50	✓	100	✓	150	✓	250	✓	500	✓
60	✓	110	✓	160	✓	275	✓		
70	✓	120	✓	170	✓	300	✓		
75	✓	125	✓	180	✓	350	✓		
80	✓	130	✓	200	✓	400	✓		