

# ETF0-Therm Insulated duct CLASS 0



## Description

Flexible pipes made from a multilayer aluminium (90%) / polyester (10%) strip, supported by a harmonic steel wire. The insulating mat, made of glass wool, density 16kg/m<sup>3</sup>, thickness 25 mm, is protected externally by an anti-condensation sleeve.

## Characteristics

Colour of inner tube: grey.  
 Colour of outer sheath: aluminium.  
 Production diameters: 80 to 610 mm.  
 Inner tube thickness: 150 micron.  
 Thickness of anti-condensation protection: 50 micron.  
 Temperature range: -20 to +250°C.  
 Bending radius: 06 x Ø.  
 Max. air speed: 32 m/s  
 Max. working pressure: 3000 Pa

## Size

Standard 10 meters.

## Use

-Air conditioning.  
 Mechanical ventilation.  
 To reduce the formation of condensation and heat dispersions.

## Reaction to fire

Certified Class 0, it meets the high regulatory requirements for fire protection.

## Price list

The length of the hose should to be considered in a extended position and at environment temperature (16/18°C - tolerance ±2%)

Item normally available from stock			
internal Ø	ETF0-Therm	internal Ø	ETF0-Therm
	euro		euro
80	✓	315	✓
102	✓	356	✓
127	✓	406	✓
152	✓	457	✓
162	✓	508	✓
203	✓	560	✓
254	✓	610	✓
305	✓		