

ESCF Circular butterfly regulation dampers heavy series for high pressures




Description

Galvanised steel circular butterfly regulation dampers installed on bushings up to a diameter of 500 mm and on bearings for diameters from 550 to 700 mm.

Characteristics

Material: galvanised steel.
Connection to the duct with tie edge (with collar).



Use

Industrial systems with high pressures.

Models

ESCF: galvanised steel;
ESCF-T: galvanised steel and shut-off butterfly;
ESCF-X: AISI 304 stainless steel;
ESCF-XT: AISI 304 stainless steel and shut-off butterfly.

Special versions

- With movement on bearings.
- Connection to duct with bayonet fitting.

On request

- Pneumatic versions;
 - electro-pneumatic versions;
 - power-operated versions;
 - modulating on/off.
- Connection to the duct with bayonet fitting or tie edge (with collar).

Dimensions and price list

model Ø	A	ESCF euro	ESCF-T euro	ESCF-X euro	ESCF-XT euro
80	150	70,40	121,00	138,60	204,60
100	150	72,60	127,60	154,00	220,00
120	150	74,80	132,00	158,40	231,00
140	150	83,60	134,20	171,60	246,40
150	170	88,00	143,00	180,40	255,20
160	170	90,20	147,40	184,80	261,80
180	170	99,00	158,40	213,40	290,40
200	220	105,60	167,20	237,60	321,20
220	220	112,20	171,60	253,00	338,80
240	250	114,40	178,20	259,60	349,80
250	250	121,00	182,60	264,00	356,40
260	250	123,20	189,20	279,40	371,80
280	300	129,80	193,60	283,80	380,60
300	300	138,60	204,60	292,60	393,80
320	300	147,40	213,40	323,40	424,60
340	350	151,80	217,80	334,40	440,00
350	350	156,20	226,60	341,00	448,80
360	350	160,60	228,80	354,20	464,20
380	400	162,80	242,00	360,80	470,80
400	400	198,00	268,40	389,40	501,60
450	400	224,40	319,00	415,80	534,60
500	400	435,60	514,80	792,00	990,00
550	400	448,80	525,80		
600	400	468,60	563,20		
650	400	528,00	682,00		
700	400	550,00	748,00		