

# ETALU-14 Flex duct with aluminium foil clipped



## Description

Flexible single-walled duct, 0.12mm thick realized with aluminum foil clipped to spiral (double very resistant crimping).

## Characteristics

Colour : aluminum  
Ribbing depth : 0,05 mm  
Temperature range: up to 300 ° C  
Curvature radius :  
- 1,2 x diameter

## Use

- Transport of hot air
- Junction for boilers, hoods, kitchens, dryers
- Connection of fume stacks and chimneys

## Size

Length of 3 m standard (compressed in packages of 0.8 m length).

## Certifications

Inflammable : Class 0

## Notes

Longer lenghts on request

## Price list

a.r. : price on request

| internal Ø | ETALU-14 | internal Ø | ETALU-14 |
|------------|----------|------------|----------|
|            | euro     |            | euro     |
| 60         | 16,69 ∨  | 140        | 24,10 ∨  |
| 70         | 18,10 ∨  | 150        | 26,67 ∨  |
| 80         | 14,20 ∨  | 160        | 28,39 ∨  |
| 90         | 15,92 ∨  | 180        | 32,91 ∨  |
| 100        | 17,40 ∨  | 200        | 37,14 ∨  |
| 110        | 19,03 ∨  | 220        | 40,57 ∨  |
| 120        | 20,61 ∨  | 250        | 50,45 ∨  |
| 125        | 21,62 ∨  | 280        | 59,54 ∨  |
| 130        | 22,79 ∨  | 300        | 66,55 ∨  |