

# ETP80-PU Flexible ducts with polyurethane sheet



## Description :

Flexible duct made of polyurethane (PU) sheet and copper plated steel wire helix (0,60 mm thickness).

## Characteristics :

Colour : transparent (blue or black on request)  
 Temperature range: from -40°C to +90°C (+125°C peaks)  
 Axial compressibility : 3:1

## Size:

Standard 20 meters. From the diameter 250mm 10 meters.

## Use :

- aspiration of chippings, wood and other material dust
- pneumatic transport of textile fibres and paper
- aspiration of pharmaceutical ingredients, foodstuff and powder food components.
- Installation in organic/chemical systems.

Peculiar characteristic of this tube is the great resistance to abrasion and cutting (5/6 times greater than rubber and 7 times more than PVC).

## Price list

The length of the hose should be considered in a extended position and at environment temperature (16/18°C - tolerance ±2%)

Item normally available from stock

internal ø	ETP80-PU euro	internal ø	ETP80-PU euro	internal ø	ETP80-PU euro	internal ø	ETP80-PU euro	internal ø	ETP80-PU euro
40	13,88 ∨	90	27,74 ∨	140	42,84 ∨	225	a.r. ∨	450	161,69 ∨
50	17,24 ∨	100	29,51 ∨	150	46,27 ∨	250	84,41 ∨	500	201,84 ∨
60	19,43 ∨	110	a.r. ∨	160	49,35 ∨	275	90,64 ∨		
70	22,80 ∨	120	33,05 ∨	170	51,92 ∨	300	101,15 ∨		
75	a.r. ∨	125	35,06 ∨	180	54,53 ∨	350	125,09 ∨		
80	24,10 ∨	130	38,96 ∨	200	59,97 ∨	400	140,45 ∨		