

# ETP80-PU Flexible ducts with polyurethane sheet



## Description :

Flexible duct made of polyurethane (PU) sheet and copper plated steel wire helix (0,60 mm thickness).

## Characteristics :

Colour : transparent (blue or black on request)  
 Temperature range: from -40°C to +90°C (+125°C peaks)  
 Axial compressibility : 3:1

## Size:

Standard 20 meters. From the diameter 250mm 10 meters.

## Use :

- aspiration of chippings, wood and other material dust
- pneumatic transport of textile fibres and paper
- aspiration of pharmaceutical ingredients, foodstuff and powder food components.
- Installation in organic/chemical systems.

Peculiar characteristic of this tube is the great resistance to abrasion and cutting (5/6 times greater than rubber and 7 times more than PVC).

## Price list

The length of the hose should be considered in a extended position and at environment temperature (16/18°C - tolerance ±2%)

Item normally available from stock

internal ø	ETP80-PU euro	internal ø	ETP80-PU euro	internal ø	ETP80-PU euro	internal ø	ETP80-PU euro	internal ø	ETP80-PU euro
40	13,88 ✓	90	27,74 ✓	140	42,84 ✓	225	a.r. ✓	450	161,69 ✓
50	17,24 ✓	100	29,51 ✓	150	46,27 ✓	250	84,41 ✓	500	201,84 ✓
60	19,43 ✓	110	a.r. ✓	160	49,35 ✓	275	90,64 ✓		
70	22,80 ✓	120	33,05 ✓	170	51,92 ✓	300	101,15 ✓		
75	a.r. ✓	125	35,06 ✓	180	54,53 ✓	350	125,09 ✓		
80	24,10 ✓	130	38,96 ✓	200	59,97 ✓	400	140,45 ✓		