

ETP100-PU Flexible ducts with polyurethane sheet



Description :

Flexible duct made of polyurethane (PU) sheet and copper plated steel wire helix (0,7 mm thickness).

Characteristics :

Colour : transparent
Temperature range: from -40°C to +80°C (+125°C peaks)
Axial compressibility : 3:1

Size:

Standard 10 meters (20 meters roll up to Ø160 on request).

Use :

- aspiration of chippings, wood and other material dust
- pneumatic transport of textile fibres and paper
- aspiration of pharmaceutical ingredients, foodstuff and powder food components.
- Installation in organic/chemical systems.

Particularly smooth inner surface suitable for heavy duty (medium level).

Price list

The length of the hose should be considered in a extended position and at environment temperature (16/18°C - tolerance ±2%)

internal ø	ETP100-PU euro	internal ø	ETP100-PU euro	internal ø	ETP100-PU euro	internal ø	ETP100-PU euro
40	24,81 ✓	80	31,89 ✓	140	54,49 ✓	275	118,33 ✓
50	26,77 ✓	90	35,75 ✓	150	58,02 ✓	300	127,31 ✓
60	28,78 ✓	100	39,68 ✓	160	66,29 ✓		
70	31,27 ✓	120	47,65 ✓	200	84,39 ✓		
75	a.r. ✓	125	49,73 ✓	250	103,63 ✓		