

ETF0-Therm Insulated duct



Description

Flexible pipes made from a multilayer aluminium (90%) / polyester (10%) strip, supported by a harmonic steel wire. The insulating mat, made of glass wool, density 16kg/m³, thickness 25 mm, is protected externally by an anti-condensation sleeve.

Characteristics

Colour of inner tube: grey.
Colour of outer sheath: aluminium.
Production diameters: 80 to 610 mm.
Inner tube thickness: 150 micron.
Thickness of anti-condensation protection: 50 micron.
Temperature range: -20 to +250°C.
Bending radius: 06 x Ø.
Max. air speed: 32 m/s
Max. working pressure: 3000 Pa

Size

Standard 10 meters.

Use

-Air conditioning.
Mechanical ventilation.
To reduce the formation of condensation and heat dispersions.

Reaction to fire

Euroclasse B-s1-d0

Price list

The length of the hose should to be considered in a extended position and at environment temperature (16/18°C - tolerance ±2%)

Item normally available from stock			
internal Ø	ETF0-Therm euro	internal Ø	ETF0-Therm euro
80	10,24 ✓	315	23,23 ✓
102	10,24 ✓	356	26,83 ✓
127	11,44 ✓	406	36,21 ✓
152	12,64 ✓	457	37,97 ✓
162	13,54 ✓	508	39,21 ✓
203	16,41 ✓	560	53,23 ✓
254	20,01 ✓	610	57,90 ✓
305	21,56 ✓		