

## EDTF Anti-freeze thermostats



### Description :

EDTF...(R) is a device with the task of controlling the temperature of heating and cooling batteries, ventilation ducts and all those applications where frost damage can be prevented.

The 15 (8) A switching contact (SPDT) allows use in a variety of functions such as controlling a fan, a shutter, an electric resistance, open or close a heating circuit or cooling circuit, start or stop a circuit pump for heating or cooling, switch off a refrigerator unit or a humidifier, signal an alarm condition through a visual or acoustic device.

### Characteristics :

Sensitive element: Copper capillar filled with gas  
Contact: SPDT microswitch  
Breaking capacity: 15 (8) A, 24...250 V AC  
Accuracy:  $\pm 1$  K  
Ambient temperature: Max. 55 °C  
Ambient humidity: 10...90 % UR (non-condensing)  
Storage temperature: -30...+60 °C  
Storage humidity: < 95 % UR  
Max. bulb temperature: 150 °C  
Casing: Base in ABS, cover in transparent polycarbonate (PC)  
Weight: 340 g  
Protection class: IP65  
Isolation class: I

### Operating data and price list

model	scale °C	stage	differential °C	reset	protection	capillar lenght m	euro
EDTF 30	from -10 to +10	1	2	automatic	IP 65	3	210,11 <a href="#">v</a>
EDTF 30R	from -10 to +10	1	-	manual	IP 65	3	220,68 <a href="#">v</a>
EDTF 60	from -10 to +10	1	2	automatic	IP 65	6	223,32 <a href="#">v</a>
EDTF 60R	from -10 to +10	1	-	manual	IP 65	6	240,50 <a href="#">v</a>