



Description :

Closed-cell cross-linked (chemical) expanded adhesive polyethylene.
 - the "nude" version looks light green
 - the "multilayer" version is externally laminated with an aluminium sheet 40 microns thickness.

Adhesive TROCELLEN EIZ-CE :

Closed-cell cross-linked (chemical) expanded adhesive polyethylene.
 MARKING :
 EURO CLASS CE (CPR) B-s2d0 and BL-s1d0 according to European standard (PEF) EN 14313:2009
 Range of thicknesses : from 3 to 12 mm

Adhesive TROCELLEN EIZ-ALU :

Multilayer polyethylene finished externally with a 40 micron smooth aluminium leaf.
 MARKING :
 EURO CLASS CE (CPR) C-s2d0 and BL-s1d0 according to European standard (PEF) EN 14313:2009
 Range of thicknesses : from 3 to 24 mm

Adhesive TROCELLEN EIZ-ALU-S-CE :

Multilayer polyethylene finished externally with a 40 micron thick smooth aluminium leaf.
 MARKING :
 EURO CLASS CE (CPR) B-s2d0 e BL-s1d0 according to European standard (PEF) EN 14313:2009
 Range of thicknesses : from 15 to 16 mm

Technical specifications	Norma	Units of Measurement	EIZ-CE	EIZ-ALU	EIZ-ALU-S-CE
Coefficient of thermal conductivity at 0°C (λ) (12 mm)	EN 12667	W/mK	0,0352	0,0358	0,0355
		kcal/mh°C	0,0303	0,0308	0,0305
Coefficient of thermal conductivity at 40°C (λ) (12 mm)	EN 12667	W/mK	0,0429	0,0435	0,0424
		kcal/mh°C	0,0369	0,0374	0,0365

Dimensions and price list

* roll height 1,5 m

a.r. : price on request

Item normally available from stock					
Thickness mm	Format sq.	Polyethylene EIZ sticker TROCELLEN EUROCLASSE CE	Polyethylene EIZ-ALU sticker TROCELLEN EUROCLASSE CE	Polyethylene EIZ-ALU-S sticker TROCELLEN EUROCLASSE CE	
		euro/sq*	euro/sq*		
3	75	7,78 ∨	16,48 ∨	-	-
6	75	10,47 ∨	18,33 ∨	-	-
8	75	13,01 ∨	20,10 ∨	-	-
10	60	15,35 ∨	21,96 ∨	-	-
12	45	17,73 ∨	23,33 ∨	-	-
14	45	-	25,34 ∨	-	-
15	45	-	25,94 ∨	a.r. ∨	-
16	a.r.	-	-	-	32,92 ∨
20	30	-	33,07 ∨	-	-
24	22.5	-	37,67 ∨	-	-