


## EDQF 4 Square diffusers with perforated front plate



### Description :

Ceiling diffuser with square perforated front plate



### Characteristics :

Aluminium perimeter frame, perforated steel plate, white RAL 9016 painting.  
Larger hole for high flow rates

### Characteristics :

Aluminium perimeter frame, perforated steel plate, white RAL 9016 painting.  
Larger hole for high flow rates

### Accessories :

- Insulated and not insulated plenum box
- Calibration damper in galvanized steel with fins with opposing movement

### Operating data and price list

Vk (m/s) : throw velocity

Q (mc/h) : airflow

Dp (Pa) pressure drop

L (m) : air throw in meters calculated on

ceiling flush installation. Terminal

velocity 0.2 m/s

| model         | effective area | air flow m <sup>3</sup> /h |      |      |      |      | euro   |
|---------------|----------------|----------------------------|------|------|------|------|--------|
|               |                | 1385                       | 1665 | 2220 | 2770 | 3325 |        |
| EDQF4 595x595 | 0,154          |                            |      |      |      |      | a.r. v |
| V m/s         |                | 2.5                        | 3    | 4    | 5    | 6    |        |
| Pa            |                | 2                          | 3    | 4    | 7    | 9    |        |
| L             |                | 2.4                        | 2.8  | 3.5  | 4.2  | 5.0  |        |
| dB(A)         |                | 16                         | 18   | 20   | 25   | 30   |        |

Item normally available from stock